

ELECTRIC STRAPPING TOOL FOR POLYPROPYLENE AND POLYESTER STRAP WITH VIBRATION SEALING



TECHNICAL SPECIFICATIONS	
DIMENSIONS	
Length	290 mm • 11.4"
Width	140 mm • 5.5"
Height	165 mm • 6.5"
Weight	3.6 Kgs • 7.9 lbs
FEEDING	
Battery	14.8V-2 A/h LI-PO
PERFORMANCE	
Max. tension force	2200N
Tensioning speed	12mt/m
Sealing	Vibration sealing
Joint strength	80% of breaking strength*

* variable according to strap type

MODEL			
CODE	TYPE	STRAP	THICKNESS
T209997	ITA20 / 13-16mm with one battery	PP-PET	0.5 mm - 0.019" • 1.05 mm - 0.041"
		13-16 mm • 1/2"-5/8"	
T2099971	ITA20 / 13-16mm with one battery and charger	PP-PET	0.5 mm - 0.019" • 1.05 mm - 0.041"
		13-16 mm • 1/2"-5/8"	
T2099972	ITA20 / 13-16mm with two batteries and charger	PP-PET	0.5 mm - 0.019" • 1.05 mm - 0.041"
		13-16 mm • 1/2"-5/8"	

POLYESTER STRAP



POLYESTER STRAP



POLYPROPYLENE STRAP

